



Rush Truck Center, Tampa FL

8111 East Adamo Dr.
Tampa, FL 33619
800-575-7383

Customer Proposal Letter

City of North Port
1930 West Price Blvd.
North Port, FL 34286
(941) 240-8060
mbramble@cityofnorthport.com
Monica Bramble

Monica Bramble, thank you for the opportunity to earn your business. We look forward to working with you on your business needs. Please accept the following proposal.

VEHICLE

Make Peterbilt Model 348 Year 2018 Stock Number To Be Determined

Additional Vehicle and Accessories Description To be delivered on or about _____

Florida Sheriffs Bid 17-VEH15.0 Spec #15 All Fees Included
2018 Peterbilt 348 chassis / 14' TBEI Ox Body

Quantity	<u>1</u>	Total
Truck Price per Unit	<u>\$125,300.00</u>	<u>\$125,300.00</u>
F.E.T. (Factory & Dealer Paid)	<u>\$0.00</u>	<u>\$0.00</u>
Net Sales Price	<u>\$125,300.00</u>	<u>\$125,300.00</u>
Optional Extended Warranty(ies)	_____	_____
State Sales Tax	_____	_____
Dealer Fee	_____	_____
Administration Fee	_____	_____
Vehicle Inventory Tax	_____	_____
Additional Taxes	_____	_____
Tire Recycling Program	<u>\$10.00</u>	<u>\$10.00</u>
Battery Disposal Fee	<u>\$3.00</u>	<u>\$3.00</u>
Out of State Vehicle Fee	_____	_____
Rebate(s)	_____	_____
Total Sales Price (Including Rebate(s))	<u>\$125,313.00</u>	<u>\$125,313.00</u>
Trade Allowance (see DISCLAIMER Below)	_____	<u>\$0.00</u>

Sales Representative	_____	Steven Bell
	signature	printed name
Purchaser	_____	_____
	signature	printed name
	_____	_____
	title	date
Accepted by Sales Manager or General Manager	_____	_____
	signature	printed name

Quote good until 9/30/2018 **Note: The above Customer Proposal is a quotation only. Sale terms subject to approval of Sales Manager of Dealer.**

DISCLAIMER: Any order based on this Proposal subject to Customer executing Dealer's standard form Retail Purchase Order incorporating above terms. Any documentary fees, state tax, title, registration and license fees subject to adjustment and change. Actual F.E.T. to be paid by Dealer, subject to adjustment. Any F.E.T. variance will be responsibility of Dealer. Manufacturer has reserved the right to change the price to Dealer of any vehicle not currently in Dealer's stock, without notice to Dealer. If Quoted Vehicle(s) not currently in Dealer's stock, Dealer reserves right to change Quotation Total to reflect any price increases from Manufacturer. This Proposal is based upon Dealer's current and expected inventory, which is subject to change. Dealer not obligated to retain any specific vehicles in stock, nor maintain any specific inventory level. Dealer shall not be obligated to fulfill Proposal in event quoted vehicle(s) not in stock or available within requested delivery schedule at time Proposal accepted. Dealer shall not be liable for any delay in providing or inability to provide Quoted Vehicle(s), where such inability or delay is due, in whole or in part, to any cause beyond the reasonable control of Dealer or is without the gross negligence or intended misconduct of Dealer. Above listed Trade Value based upon current appraisal of Trade Vehicle(s). Dealer may adjust Trade Value of Trade Vehicle(s) to reflect changes in condition and/or mileage of Trade Vehicle(s) between date of current appraisal and acceptance of this Proposal by Customer.



Rush Truck Center - Orlando HD P475
1925 Princeton Street

City of North Port
1930 West Price Boulevard

Orlando, Florida United States 34804
Phone:
Fax:
Email:

North Port, Florida United States 34268
Phone: (407) 774-0800
Fax:
Contact Email: rheseler@cityofnorthport.com
Prepared for: Ralf Heseler

Vehicle Summary

Unit		Chassis	
Model:	Model 348	Fr Axle Load (lbs):	14600
Type:	Full Truck	Rr Axle Load (lbs):	44000
Description:	2018 348 Dump Spec	G.C.W. (lbs):	58600
Application		Road Conditions:	
Intended Serv.:	Construction Dump-On/Off Highway	Class A (Highway)	95
Commodity:	Construction Materials	Class B (Hwy/Mtn)	0
Body		Class C (Off-Hwy)	5
Type:	End Dump	Class D (Off-Road)	0
Length (ft):	14	Maximum Grade:	6
Height (ft):	12.5	Wheelbase (in):	184
Max Laden Weight (lbs):	5500	Overhang (in):	62.7
Trailer		Fr Axle to BOC (in):	69.8
No. of Trailer Axles:	0	Cab to Axle (in):	114.2
Type:		Cab to EOF (in):	176.9
Length (ft):	0	Overall Comb. Length (in):	285
Height (ft):	0.0	Special Req.	
Kingpin Inset (in):	0	United States Registry	
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

	Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com .
	PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	11/1/2017 1:40:22 PM	Complete	Model Number:	Model 348
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q13947457
Prepared by:	ID: SteveBell		Version Number:	35.20



Rush Truck Center - Orlando HD P475
1925 Princeton Street

City of North Port
1930 West Price Boulevard

Orlando, Florida United States 34804
Phone:
Fax:
Email:

North Port, Florida United States 34268
Phone: (407) 774-0800
Fax:
Contact Email: rheseler@cityofnorthport.com
Prepared for: Ralf Heseler

	Description	Weight
Base Model		
	Model 348	10,610
	Construction Materials	0
	Construction Dump-On/Off Highway Truck or tractor without liftable trailing axle which carries bulk materials (excavated earth, sand/gravel, asphalt, demolition debris, etc.) and unloads by dumping out the back, over the side of the body, or out the bottom of the trailer.	0
	End Dump	0
	United States Registry	0
Configuration		
	Not Applicable Secondary Manufacturer	0
Frame & Equipment		
	10-5/8in Steel Rails to 285in 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	135
	Full Steel Inner Liner	514
	Custom Wheelbase or Overhang Engineering approval may be required.	0
	Three-Piece Crossmembers	0
	EOF Square without Xmbr For use with body builder installed crossmember.	0
	Omit Rear Mudflaps and Hangers	0
Front Axle & Equipment		
	Dana Spicer E1462I 14,600 lb, 3.5 in. Drop Factory front axle alignment to improve handling & reduce tire wear. Zerk fittings on tie rod ends, king pins, & draglink ball joints for ease of maintenance & help extend service life of components. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	28

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	11/1/2017 1:40:22 PM	Complete	Model Number:	Model 348
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q13947457
Prepared by:	ID: SteveBell		Version Number:	35.20



Description	Weight
Taper Leaf Springs, Shocks 14,600 lb	57
Power Steering Sheppard SD110 For use with 14,600 lb. axle ratings	0
Power Steering Reservoir Frame Mounted	0
PHP10 Aluminum LMS Hubs 11-1/4in bolt circle. Includes a supplier extended coverage up to 3 years / 350,000 miles for bearings & seals.	0
Bendix Air Cam Front Drum Brakes 16.5x5 For use with 10,000 lbs to 14,600 lbs steer axles. Includes automatic slack adjusters & outboard mounted brake drums.	0
Gusseted Cam Brackets, Steer Axle	0

Rear Axle & Equipment

Dana Spicer DSH44 44,000 lb, High Performance 44 Interaxle diff lock air rocker occupies space of one gauge. 12.5 mm housing, 15.75 ring gear. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	2,010
PHP10 Iron LMS Hubs 11-1/4" bolt circle. Includes a supplier extended coverage up to 3 years / 350,000 miles for bearings & seals.	0
Standard Stroke Parking Brakes Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car Carriers.	0
Diff Lock Both Axles (Air Rocker Switch occupies the space of one gauge)	60
Lube Pump, Drive Axle(s)	36
Gusseted Cam Brackets, Drive Axle(s)	2
SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0
Stability System Not Selected or Not Available	0
Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	11/1/2017 1:40:22 PM	Complete	Model Number:	Model 348
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q13947457
Prepared by:	ID: SteveBell		Version Number:	35.20



Description	Weight
Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0
Bendix Air Cam Rear Drum Brakes 16.5x8.6 Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums. Refer to TSB 11-57 for more information.	0
Tandem Drive Axle (Model 348)	0
Ratio 5.57 Rear Axle	0
Peterbilt Air Trac 44,000 lb, 52in Axle Spacing Light Weight	505
Dash Mtd Dump Switch With Indicator Light For suspension	2

Engine & Equipment

PACCAR PX-9 350@2000 GOV@2200 1150@1400 Productivity (2017 Emissions) Includes alum flywheel housing, cruise control, and J1939 provisions (provides an interface point for the Electronic Service Analysis-ESA and other PACCAR approved diagnostic tools). Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life.	0
N21320 N205 120..Standard Maximum Speed Limit [LSL]	
N21330 N207 0....Expiration Distance	
N21340 P005 120..Hard Maximum Speed Limit	
N21350 P001 68...Maximum Accelerator Pedal Vehicle Speed	
N21370 P059 68...Maximum Cruise Speed	
N21400 N203 252..Reserve Speed Function Reset Distance	
N21410 N202 0....Maximum Cycle Distance	
N21420 N206 10...Maximum Active Distance	
N21430 N201 0....Reserve Speed Limit Offset	
N21440 P015 NO...Engine Protection Shutdown	
N21450 P026 NO...Gear Down Protection	
N21460 P046 1400.Max PTO Speed	
N21470 P062 NO...Cruise Control Auto Resume	
N21480 P068 NO...Auto Engine Brake in Cruise	
N21500 N209 0....Expiration Distance	
N21510 P520 YES..Enable Idle Shutdown Park Brake Set	
N21520 P030 5....Timer Setting	
N21530 P233 YES..Enable Impending Shutdown Warning	
N21540 P234 60...Timer For Impending Shutdown Warning	
N21550 P516 35...Engine Load Threshold	
N21570 P031 NO...Idle Shutdown Manual Override	
N21590 P230 YES..Enable Hot Ambient Automatic Override	
N21610 P172 40...Low Ambient Temperature Threshold	
N21620 P173 60...Intermediate Ambient Temperature Threshold	

**Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.**

Printed:	11/1/2017 1:40:22 PM	Complete	Model Number:	Model 348
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q13947457
Prepared by:	ID: SteveBell		Version Number:	35.20



Description	Weight
N21630 P171 80...High Ambient Temperature Threshold	
Engine Idle Shutdown Timer Disabled	0
Enable EIST Ambient Temp Override	0
Eff EIST NA Expiration Miles	0
Effective VSL Setting NA	0
Remote PTO And Throttle Provision	0
CARB Engine Idling Compliance DECLINED By Dealer/Customer	0
PACCAR 160 Amp Alternator, Brushed	0
Immersion Type Block Heater 110-120V Standard location is center left hand under cab and includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	2
PACCAR 12V Starter	0
2 PACCAR Premium 12V Starting Batteries 2000 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0
Kissling Battery Disconnect Switch Mounted on battery box	3
2-Speed Fan Clutch For Frequent Start/Stops	0
18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0
Spin-On Fuel/Water Separator	0
No Fluid Heat Option for Fuel Filter	0
No Electric Heat Option for Fuel Filter	0
Engine Protection Shutdown Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	0
High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 587: 1330 sq in, 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 384/386: 1301 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 320: 1242 sq in.	0
Radial Seal, Dry Type Air Cleaner, Frontal Air Intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0

**Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.**

Printed:	11/1/2017 1:40:22 PM	Complete	Model Number:	Model 348
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q13947457
Prepared by:	ID: SteveBell		Version Number:	35.20



Description	Weight
Exhaust Single RH Side Of Cab DPF/SCR RH Under Cab (2017).	29
Curved Tip Standpipe(s)	0
18in Ht, 5in Dia Chrome, Clear Coat Standpipe(s)	-2

Transmission & Equipment

Allison 3000 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, TranSynd Automatic Transmission Fluid, and Water Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. (Suited for vehicles operating on/off highway and/or requiring PTO operation) Forward Ratios: 1st-3.49, 2nd-1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65 / Reverse Ratios: DR-(5.03)	110
1760 HD Driveline, 1 Midship Bearing	-20
(1) Dash Mounted Single Acting Air PTO Control Standard with PTO engaged indicator light on Class 8 units. Occupies the space of one gauge. Specing PTO switch does not ensure the PTO will fit.	0
Allison FuelSense Not Desired	0
Auto Neutral Activates With Parking Brake	0
Allison 6-Speed Configuration, Close Ratio Gears 3000 Series Transmissions	0
Allison Output Function S Neutral Indicator For PTO. Required on Refuse Packer Applications. With this configuration NEUTRAL only, PTO engagement is permitted only when the transmission is in Neutral. Once the transmission is in Neutral, the PTO is automatically engaged and fast idle is initiated when the PTO switch is switched On. Also, with this configuration Pack-on-the-fly, the PTO is automatically engaged and fast idle is initiated when the PTO switch is On concurrently with shifting of the transmission to Neutral.	0
Dash Mounted Push Button Shifter	0

Air & Trailer Equipment

Bendix AD-IS EP Air Dryer with Heater And Coalescing Filter; Extended Purge	0
Pull Cords All Air Tanks	0
Nylon Chassis Hose	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	11/1/2017 1:40:22 PM	Complete	Model Number:	Model 348
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q13947457
Prepared by:	ID: SteveBell		Version Number:	35.20



Description	Weight
Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0
Clear Outside Frame of All Air System Components RH BOC	0
Clear Inside Frame of All Air System Components RH BOC	0
Wiring Provision For F/O Brake Controller For trucks that have trailer connections tailored to the light trailer with cab pre-wire for trailer brake controllers. Not available with option 4620080.	0
Body Connections 5ft BOC Junction Box contains light and power circuits for Body Connections located 5ft from BOC.	4
Trailer Hand Valve	11
A&E Conn EOF w/7-way Socket (w/Conn EOF Strapped to the rail)	15
Tires & Wheels	
FF: BR 20ply 315/80R22.5 M843 MSI 65 MPH Max Speed Rating; Diameter = 43.3 inches; SLR = 20.1 inches	90
RR: BR 16ply 11R22.5 M843 Diameter = 42.5 inches; SLR = 19.9 inches	192
Code-rear Tire Qty 08	0
FF: Accur Stl Armor 29039PK 22.5X9.00 PHP10-5 Hand Holes	74
RR: Accur Stl Armor 50291PK 22.5X8.25 Heavy Duty, Two Hand Holes	136
Code-rear Rim Qty 08	0
Fuel Tanks	
23in Aluminum 70 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	9
Location LH U/C 70 Gallon	0
Polish (1) Non-Slip Fuel Tank Step, U/C Tank Only	0
DEF Tank Mounted LH BOC Models 210, 220 and 320 mounted LH cab fender.	0
Standard DEF To Fuel Ratio 2:1 Or Greater	0
DEF Tank Small	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	11/1/2017 1:40:22 PM	Complete	Model Number:	Model 348
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q13947457
Prepared by:	ID: SteveBell		Version Number:	35.20



	Description	Weight
Battery Box & Bumper		
	Aluminum Space Saver Battery Box RH BOC Battery Access From Side	-84
	Rubber Battery Pad In Bottom Of (1) Battery Box (Mat in box that holds batteries only)	2
	Aftertreatment RH U/C Alum Non-Slip Cab Entry Step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box will be aerodynamic.	0
	Steel Styled Aero Bumper Chrome Two Tow Pins	0
Cab & Equipment		
	Alum Cab 108in BBC Metton Hood w/Bright Crown Includes view window RH door and convex mirror over RH door.	0
	Severe Service Cab Package #1 Includes Aluminum side skins, aluminum rear skin, steel windshield mask, steel firewall, and steel front floor sheet on all cabs, and additional reinforcement structure on the back wall of the day cab.	39
	Thermal Insulation Package in Cab Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure.	2
	Rubber Fender Lips 2 Inch Wide	8
	Peterbilt UltraRide Driver Seat	0
	Peterbilt UltraRide Passenger Seat	0
	Drivers Armrest - RH Only Required in Model 587 with Evolution LX seats. Optional with Evolution ST and Rolltek Seats.	2
	Passenger Armrest - LH only Required with Evolution LX seats, optional with Evolution ST Seats.	2
	Air Ride Driver	0
	High Back Driver	0
	Vinyl Driver	0
	Non-Air Ride Passenger	0
	High Back Passenger	0
	Vinyl Passenger	0
	Adjustable Steering Column - Tilt/Telescope	11
	Steering Wheel with Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	11/1/2017 1:40:22 PM	Complete	Model Number:	Model 348
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q13947457
Prepared by:	ID: SteveBell		Version Number:	35.20



Description	Weight
Interior Grey/Black Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash.	0
Dark Window Tint ipo STD Tint - Day Cab	0
Extended Rear Window ipo Std Window-Day Cab The extended rear window protrudes two inches more than the standard conventional rear cab window. Take this into consideration when determining your loadspace.	0
Day Cab Rear Window	0
One Piece Curved Windshield	0
Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0
Cup Holder (Floor Mounted) Includes two standard-size drink holders and one extra-large jugholder, coin tray, and clipboard-size storage area.	4
Peterbilt Comfort Control - Cab	6
Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper or furnished by owner sleeper.	4
Stainless Steel Mirrors 7x16 with Heat Element Right Click on Option to see Picture in Product Portfolio.	2
(2) Convex 8 Inch SS Mirror Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops.	4
Power Package Includes power door locks and power windows.	0
(1) Air Horn 15in Painted Mounted under cab.	8
Standard Speaker Package For Cab (2) Speakers	4
ConcertClass w/CD, Bluetooth Phone and Audio Includes AM/FM, WB, USB and MP3.	10
Radio Antenna Mounted on RH Mirror Bracket	0
Power Wire Under Dash for F/O Cellular Phone Without antenna. Not available with Rami Antenna System.	0
Plug-In Auto Reset Circuit Breaker in place of fuses in junction box.	0

Unpublished options may require review/approval.
 Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	11/1/2017 1:40:22 PM	Complete	Model Number:	Model 348
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q13947457
Prepared by:	ID: SteveBell		Version Number:	35.20



Description	Weight
Peterbilt Electric Windshield Wipers With Intermittent Feature.	0
CabMate Cab Air Suspension Mfg by Link. The class 8 conventionals (except Model 348) includes (2) airbags, (2) shock absorbers, (1) leveling valve, radius rod, and height limiter. The Models 330, 337, and 348 includes (1) airbag and (1) shock absorber.	15
Triangle Reflector Kit Shipped Loose	13
Fire Extinguisher; Cab Mounted Hazmat approved UL listed/rated ABC.	8
Main Transmission Oil Temperature Gauge Located in Driver Information Display	0
Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall.	0
Bright Bezel Gauges	0
(1) Additional Electric Switch Without Wiring	0
Main Instrumentation Panel, Graphics Display Includes speedometer with trip odometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights w/audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.	0
Headlights Composite Fender Mounted Integral Park, Turn, and Side Marker	0
(5) Marker Lights, Aero LED Light Emitting Diodes	0
Switch And Wiring For F/O Beacon/Strobe 10ft coiled wire BOC/BOS at rear sill.	2
LED Stop/Turn/Tail/Backup Bracket mounted LH/RH EOF	2
Moveable EOF Xmbr For Mounting Taillights Square EOF with or without EOF xmbr.	10

Paint

Standard Paint Color Selection	0
(1) Color Axalta Two Stage - Cab/Hood	0
Base Coat/Clear Coat	
N85020 A - L0006EY WHITE - STAND	
N85400 HOOD TOP L0006EY WHITE - STAND	
N85500 CAB ROOF L0006EY WHITE - STAND	
N85200 FRAME N0001EA BLACK	

**Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.**

Printed:	11/1/2017 1:40:22 PM	Complete	Model Number:	Model 348
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q13947457
Prepared by:	ID: SteveBell		Version Number:	35.20



	Description	Weight
	N85300 FENDER L0006EY WHITE - STAND	
Options Not Subject To Discount		
	Chassis to Receive Extended Warranty 1 Year Base Vehicle Towing - US. No Additional Extended Warranty is Required.	0
Miscellaneous		
	2017 EPA Emissions Engine Warranty Only	0
	Presentation Created Using Featured Spec For Model	0
Total Weight		14686

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	11/1/2017 1:40:22 PM	Complete	Model Number:	Model 348
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q13947457
Prepared by:	ID: SteveBell		Version Number:	35.20



TRUCK BODIES & EQUIPMENT INTERNATIONAL, Inc.
Ox Bodies | Crysteel | DuraClass | Rugby | J-Craft | Hardee

Quote Response Form

Page 1 of 3
10/30/2017 06:34 PM

TBEI - Ox Bodies
719 Columbus Street East
PO Box 886
Fayette AL 35555
USA
800-844-2519

End User: CITY OF NORTHPORT, FL
Customer: 104867
Steve Bell
RUSH TRUCK CENTER- TAMPA
8111 East Adamo Drive
Tampa FL 33619
USA

Taken By: Kevin Griggs

Phone: 321-205-7143

Fax: 830-626-5311

Estimate	Terms	Quote Date	Expiration Date	Salesperson	Customer Currency
FA00087163	Net 30 Days			VAN DYKE, RAY	USD

UM	Quantity	Item	Description	Unit Price	Extended Price
EA	1.00	1871438	MV85-1400-1315YD-63108-50/40/48STR-STD-T	12,938.00	12,938.00



TRUCK BODIES & EQUIPMENT INTERNATIONAL, Inc.
 Ox Bodies | Crysteel | DuraClass | Rugby | J-Craft | Hardee

Quote Response Form

Estimate	Terms	Quote Date	Expiration Date	Salesperson	Customer	Currency
FA00087163	Net 30 Days			VAN DYKE, RAY		USD

UM	Quantity	Item	Description	Unit Price	Extended Price
----	----------	------	-------------	------------	----------------

Body Style: Maverick
 Body Length: 14'
 Hoist Model: 63108
 Frame Style: Tube w/X-Mem 12 C/L
 Rear Style: Straight
 Front Exhaust Notch: No
 Front Height: 50
 Side Height Front: 40
 Side Height Rear: 40
 Rear Height: 48
 Side Material: 10GA CS
 Front Material: 10GA CS
 Tailgate Material: 7GA CS
 Floor Material: 1/4" plate
 Cabshield Style: Standard
 Cabshield Projection: 24
 Cabshield Width: 85
 Tarp Style: Mountain
 Tailgate Type: Standard
 Tailgate Bracing Style: 1 Horizontal
 Coal Chute- None
 Horizontal Side Brace: No
 Side Top Rail Style: Standard
 Dump Assist Vibrator: No
 Dump Apron: Standard
 Dump Apron Size: 10
 Side Light Cutouts: Lower Front & Rear Clearance
 Metro Light Quantity: 1
 Dirt Shedding Angle: No
 Board Holder Height: 8

Cab Height 70"
 Hydraulic Tank: 1250596-Pyramid Flat Bottom Standard
 Rear Hinge: 1347238-Standard
 Hoist: 63108
 Paint: Black ***PAINT BOARDS***
 Cab Controls: 1250507-Electric Shift PTO/Cable Shift Pump, Auto Trans, Electric Tarp/Mountain
 Pump: 1249981-Cable Shift, Auto, Pump G102-D1-2.0(073) C/W ROT
 PTO: 1249994-PTO KIT ELEC AT CS20-A1007-H3KX PHINST
 Side Boards: 1248918-Wood 8" - Up to 17' body
 Mud Flaps: 1250013-Standard Mud Flaps
 Backup Alarm: 1248915-Back-Up Alarm
 Light Kit: Standard
 Truck Model: Peterbilt
 Yardage: 12-14



TRUCK BODIES & EQUIPMENT INTERNATIONAL, Inc.
Ox Bodies | Crysteel | DuraClass | Rugby | J-Craft | Hardee

Quote Response Form

TBEI - Ox Bodies
719 Columbus Street East
PO Box 886
Fayette AL 35555
USA
800-844-2519

End User: CITY OF NORTHPORT, FL
Customer: 104867
Steve Bell
RUSH TRUCK CENTER- TAMPA
8111 East Adamo Drive
Tampa FL 33619
USA

Taken By: Kevin Griggs

Phone: 321-205-7143
Fax: 830-626-5311

Estimate	Terms	Quote Date	Expiration Date	Salesperson	Customer Currency
FA00087163	Net 30 Days			VAN DYKE, RAY	USD

UM	Quantity	Item	Description	Unit Price	Extended Price
EA	1.00	1249365	TARP ELEC MT MESH N/FL AL 10-16 INST	927.00	927.00
EA	1.00	1751287	HITCH 22" 45TON W/GLADS 7-PIN INSTALL	1,133.00	1,133.00
EA	1.00	1250067	ELECTRIC BRAKE CONTROL INSTALL	309.00	309.00

**By signing below I acknowledge that I have reviewed the specs above and confirmed they are correct. I understand that once my order is placed and sent into production that I will not be able to make changes to the order. I assume full ownership of the body once production begins.

X _____

VIN _____ TRANS _____

ETA _____ DUMP BODY COLOR _____

Gross Sales:	15,616.00
Order Disc	309.00
Sale Amount:	15,307.00
Freight:	1,700.00
Sales Tax:	0.00
FET Charges:	0.00
Total Amount:	17,007.00