



2840 Center Port Circle  
Pompano, Bch, FL. 33064



Freightliner  
**SPRINTER**



PURCHASER: \_\_\_\_\_ DATE: \_\_\_\_\_

ADDRESS: \_\_\_\_\_ PHONE: \_\_\_\_\_

CITY: \_\_\_\_\_ ATTN: \_\_\_\_\_

BASE MODEL: \_\_\_\_\_ PRICE: \_\_\_\_\_

OPTION # \_\_\_\_\_ PRICE: \_\_\_\_\_

OPTION # \_\_\_\_\_ PRICE: \_\_\_\_\_

OPTION # \_\_\_\_\_ PRICE: \_\_\_\_\_

OPTION # \_\_\_\_\_ PRICE: \_\_\_\_\_

OPTION # \_\_\_\_\_ PRICE: \_\_\_\_\_

OPTION # \_\_\_\_\_ PRICE: \_\_\_\_\_

OPTION # \_\_\_\_\_ PRICE: \_\_\_\_\_

OPTION # \_\_\_\_\_ PRICE: \_\_\_\_\_

OPTION # \_\_\_\_\_ PRICE: \_\_\_\_\_

OPTION # \_\_\_\_\_ PRICE: \_\_\_\_\_

OPTION # \_\_\_\_\_ PRICE: \_\_\_\_\_

OPTION # \_\_\_\_\_ PRICE: \_\_\_\_\_

OPTION # \_\_\_\_\_ PRICE: \_\_\_\_\_

### Budget Challenges?

Daimler Truck Financial offers special municipal financing programs to help fund the purchase of needed vehicles and other equipment.

**TOTAL PRICE:** \_\_\_\_\_

**\*MTHLY PAYMENT:** \_\_\_\_\_

- Monthly, annual, semi-annual or quarterly payment options
- Flexible repayment terms (tied to your budget)

\*Actual rate, terms, down payment, and program eligibility will be determined by DTF credit team based upon credit worthiness and experience of customer.

2017/2018 FLORIDA SHERIFFS  
 CONTRACT SPEC 13  
 LOU BACHRODT FREIGHTLINER LOW  
 BID ON THIS SPEC.

Prepared by:  
 Drew Ellison  
 LOU BACHRODT FREIGHTLINER  
 SBL FREIGHTLINER  
 2840 CENTER PORT CIRCLE  
 POMPANO BEACH, FL 33064  
 Phone: 407-886-6704

# NORTH PORT CITY OF

## HD IND POT HOLE PATCH UNIT

### QUOTATION

#### M2 106 CONVENTIONAL CHASSIS

SET BACK AXLE - TRUCK	DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74 DROP
CUM B6.7 280 HP @ 2400 RPM, 2600 GOV, 660 LB/FT @ 1600 RPM	SINGLE FRONT AXLE
ALLISON 3500 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION	12,000# MONO TAPERLEAF FRONT SUSPENSION
RS-21-160 21,000# R-SERIES SINGLE REAR AXLE	154 INCH BBC HIGH-ROOF ALUMINUM CONVENTIONAL CREW CAB
23,000# 52 INCH VARIABLE RATE MULTI-LEAF SPRING REAR SUSPENSION WITH LEAF SPRING HELPER	6100MM (240 INCH) WHEELBASE
	11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI
	1425MM (56 INCH) REAR FRAME OVERHANG

		PER UNIT	TOTAL
VEHICLE PRICE	TOTAL # OF UNITS (1)	\$	\$
EXTENDED WARRANTY		\$	\$
DEALER INSTALLED OPTIONS		\$	\$
<b>CUSTOMER PRICE BEFORE TAX</b>		<b>\$</b>	<b>\$</b>

#### TAXES AND FEES

TAXES AND FEES	\$	0	\$	0
OTHER CHARGES	\$	0	\$	0

#### TRADE-IN

TRADE-IN ALLOWANCE	\$	(0)	\$	(0)
--------------------	----	-----	----	-----

<b>BALANCE DUE</b>	<b>(LOCAL CURRENCY)</b>	<b>\$</b>	<b>155,210</b>	<b>\$</b>	<b>155,210</b>
--------------------	-------------------------	-----------	----------------	-----------	----------------

#### COMMENTS:

Projected delivery on \_\_\_ / \_\_\_ / \_\_\_ provided the order is received before \_\_\_ / \_\_\_ / \_\_\_.

#### APPROVAL:

Please indicate your acceptance of this quotation by signing below:

Customer: X\_\_\_\_\_ Date: \_\_\_ / \_\_\_ / \_\_\_.

2017/2018 FLORIDA SHERIFFS  
CONTRACT SPEC 13  
LOU BACHRODT FREIGHTLINER LOW  
BID ON THIS SPEC.

**Prepared by:**  
Drew Ellison  
LOU BACHRODT FREIGHTLINER  
SBL FREIGHTLINER  
2840 CENTER PORT CIRCLE  
POMPANO BEACH, FL 33064  
Phone: 407-886-6704

**Daimler Truck Financial**

Financing that works for you.

See your local dealer for a competitive quote from Daimler Truck Financial, or contact us at [Information@dtfoffers.com](mailto:Information@dtfoffers.com).

Daimler Truck Financial offers a variety of finance, lease and insurance solutions to fit your business needs. For more information about our products and services, visit our website at [www.daimler-truckfinancial.com](http://www.daimler-truckfinancial.com).

## S P E C I F I C A T I O N   P R O P O S A L

Description
<b>Price Level</b>
M2 PRL-10M (EFF:02/11/15)
<b>Data Version</b>
SPECPRO21 DATA RELEASE VER 025
<b>Interior Convenience/Driver Retention Package</b>
NO INTERIOR CONVENIENCE PACKAGE
<b>Vehicle Configuration</b>
M2 106 CONVENTIONAL CHASSIS SET BACK AXLE - TRUCK STRAIGHT TRUCK PROVISION LH PRIMARY STEERING LOCATION
<b>General Service</b>
TRUCK CONFIGURATION DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES) PICKUP AND DELIVERY/SHORT HAUL SERVICE GOVERNMENT BUSINESS SEGMENT FIXED LOAD COMMODITY TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS MAXIMUM 8% EXPECTED GRADE SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE MEDIUM TRUCK WARRANTY EXPECTED FRONT AXLE(S) LOAD : 12000.0 lbs EXPECTED REAR DRIVE AXLE(S) LOAD : 21000.0 lbs EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 33000.0 lbs

**Description**

**Truck Service**

FLATBED/PLATFORM/STAKE BODY  
 GODWIN MANUFACTURING COMPANY  
 EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE  
 FRAME "XX" INCHES : 32.0 in

**Engine**

CUM B6.7 280 HP @ 2400 RPM, 2600 GOV, 660  
 LB/FT @ 1600 RPM

**Electronic Parameters**

75 MPH ROAD SPEED LIMIT  
 CRUISE CONTROL SPEED LIMIT SAME AS ROAD  
 SPEED LIMIT  
 PTO MODE BRAKE OVERRIDE - SERVICE  
 BRAKE APPLIED  
 PTO RPM WITH CRUISE SET SWITCH - 700 RPM  
 PTO RPM WITH CRUISE RESUME SWITCH - 800  
 RPM  
 PTO MODE CANCEL VEHICLE SPEED - 5 MPH  
 PTO GOVERNOR RAMP RATE - 250 RPM PER  
 SECOND  
 PTO MINIMUM RPM - 700  
 REGEN INHIBIT SPEED THRESHOLD - 5 MPH  
 ONE (1) REMOTE PTO SET SPEED

**Engine Equipment**

2016 ONBOARD DIAGNOSTICS/2010  
 EPA/CARB/FINAL GHG17 CONFIGURATION  
 2008 CARB EMISSION CERTIFICATION - CLEAN  
 IDLE (INCLUDES 6X4 INCH LABEL ON LOWER  
 FORWARD CORNER OF DRIVER DOOR)  
 STANDARD OIL PAN  
 ENGINE MOUNTED OIL CHECK AND FILL  
 ONE PIECE VALVE COVER  
 SIDE OF HOOD AIR INTAKE WITH DONALDSON  
 HIGH CAPACITY AIR CLEANER WITH SAFETY  
 ELEMENT, FIREWALL MOUNTED  
 DR 12V 160 AMP 28-SI QUADRAMOUNT PAD  
 ALTERNATOR WITH REMOTE BATTERY VOLT  
 SENSE

---

**Description**

---

(2) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT  
MAINTENANCE FREE 2250 CCA THREADED  
STUD BATTERIES  
BATTERY BOX FRAME MOUNTED  
STANDARD BATTERY JUMPERS  
SINGLE BATTERY BOX FRAME MOUNTED LH  
SIDE UNDER CAB  
WIRE GROUND RETURN FOR BATTERY CABLES  
WITH ADDITIONAL FRAME GROUND RETURN  
NON-POLISHED BATTERY BOX COVER  
POSITIVE LOAD DISCONNECT WITH CONTROL  
SWITCH WITH LOCKING PROVISION MOUNTED  
OUTSIDE OF CAB  
CUMMINS TURBOCHARGED 18.7 CFM AIR  
COMPRESSOR WITH INTERNAL SAFETY VALVE  
STANDARD MECHANICAL AIR COMPRESSOR  
GOVERNOR  
AIR COMPRESSOR DISCHARGE LINE  
ELECTRONIC ENGINE INTEGRAL SHUTDOWN  
PROTECTION SYSTEM  
RH OUTBOARD UNDER STEP MOUNTED  
HORIZONTAL AFTERTREATMENT SYSTEM  
ASSEMBLY WITH RH HORIZONTAL TAILPIPE  
ENGINE AFTERTREATMENT DEVICE,  
AUTOMATIC OVER THE ROAD REGENERATION  
AND DASH MOUNTED REGENERATION  
REQUEST SWITCH  
STANDARD EXHAUST SYSTEM LENGTH  
RH STANDARD HORIZONTAL TAILPIPE  
6 GALLON DIESEL EXHAUST FLUID TANK  
100 PERCENT DIESEL EXHAUST FLUID FILL  
LH MEDIUM DUTY STANDARD DIESEL EXHAUST  
FLUID TANK LOCATION  
STANDARD DIESEL EXHAUST FLUID PUMP  
MOUNTING  
STANDARD DIESEL EXHAUST FLUID TANK CAP  
HORTON HT650 FRONTAL AIR ON/OFF ENGINE  
FAN CLUTCH  
AUTOMATIC FAN CONTROL WITHOUT DASH  
SWITCH, NON ENGINE MOUNTED  
CUMMINS SPIN ON FUEL FILTER  
FULL FLOW OIL FILTER  
950 SQUARE INCH ALUMINUM RADIATOR

#### Description

ANTIFREEZE TO -34F, ETHYLENE GLYCOL PRE-CHARGED SCA HEAVY DUTY COOLANT  
 GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT  
 CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES  
 RADIATOR DRAIN VALVE  
 LOWER RADIATOR GUARD  
 ALUMINUM FLYWHEEL HOUSING  
 ELECTRIC GRID AIR INTAKE WARMER  
 DELCO 12V 38MT HD STARTER WITH INTEGRATED MAGNETIC SWITCH

#### Transmission

ALLISON 3500 RDS AUTOMATIC TRANSMISSION  
 WITH PTO PROVISION

#### Transmission Equipment

ALLISON VOCATIONAL PACKAGE 145 -  
 AVAILABLE ON 3000/4000 PRODUCT FAMILIES  
 WITH VOCATIONAL MODEL RDS  
 ALLISON VOCATIONAL RATING FOR ON/OFF  
 HIGHWAY APPLICATIONS AVAILABLE WITH ALL  
 PRODUCT FAMILIES  
 PRIMARY MODE GEARS, LOWEST GEAR 1,  
 START GEAR 1, HIGHEST GEAR 6, AVAILABLE  
 FOR 3000/4000 PRODUCT FAMILIES ONLY  
 SECONDARY MODE GEARS, LOWEST GEAR 1,  
 START GEAR 1, HIGHEST GEAR 6, AVAILABLE  
 FOR 3000/4000 PRODUCT FAMILIES ONLY  
 PRIMARY SHIFT SCHEDULE RECOMMENDED BY  
 DTNA AND ALLISON, THIS DEFINED BY ENGINE  
 AND VOCATIONAL USAGE  
 SECONDARY SHIFT SCHEDULE  
 RECOMMENDED BY DTNA AND ALLISON, THIS  
 DEFINED BY ENGINE AND VOCATIONAL USAGE  
 PRIMARY SHIFT SPEED RECOMMENDED BY  
 DTNA AND ALLISON, THIS DEFINED BY ENGINE  
 AND VOCATIONAL USAGE  
 SECONDARY SHIFT SPEED RECOMMENDED BY  
 DTNA AND ALLISON, THIS DEFINED BY ENGINE  
 AND VOCATIONAL USAGE  
 LOAD BASED SHIFT SCHEDULE AND VEHICLE  
 ACCELERATION CONTROL RECOMMENDED BY  
 DTNA AND ALLISON, THIS DEFINED  
 VOCATIONAL USAGE

#### Description

NEUTRAL AT STOP - DISABLED, FUELSENSE -  
 DISABLED  
 DRIVER SWITCH INPUT - DEFAULT - NO  
 SWITCHES  
 TCU-DIRECTION CHNG,NOT CONFIGURED  
 TCU-PUMP MODE OPTION NOT CONFIGURED  
 TCU-RANGE INDICATION NOT CONFIGURED  
 VEHICLE INTERFACE WIRING CONNECTOR  
 WITHOUT BLUNT CUTS, AT BACK OF CAB  
 ELECTRONIC TRANSMISSION CUSTOMER  
 ACCESS CONNECTOR FIREWALL MOUNTED  
 CUSTOMER INSTALLED CHELSEA 277 SERIES  
 PTO  
 PTO MOUNTING, LH SIDE OF MAIN  
 TRANSMISSION  
 MAGNETIC PLUGS, ENGINE DRAIN,  
 TRANSMISSION DRAIN, AXLE(S) FILL AND  
 DRAIN  
 PUSH BUTTON ELECTRONIC SHIFT CONTROL,  
 DASH MOUNTED  
 TRANSMISSION PROGNOSTICS - ENABLED 2013  
 WATER TO OIL TRANSMISSION COOLER, IN  
 RADIATOR END TANK  
 TRANSMISSION OIL CHECK AND FILL WITH  
 ELECTRONIC OIL LEVEL CHECK  
 SYNTHETIC TRANSMISSION FLUID (TES-295  
 COMPLIANT)

#### Front Axle and Equipment

DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74  
 DROP SINGLE FRONT AXLE  
 MERITOR 15X4 Q+ CAM FRONT BRAKES  
 NON-ASBESTOS FRONT BRAKE LINING  
 CONMET CAST IRON FRONT BRAKE DRUMS  
 FRONT BRAKE DUST SHIELDS  
 FRONT OIL SEALS  
 VENTED FRONT HUB CAPS WITH WINDOW,  
 CENTER AND SIDE PLUGS - OIL  
 STANDARD SPINDLE NUTS FOR ALL AXLES  
 MERITOR AUTOMATIC FRONT SLACK  
 ADJUSTERS  
 TRW THP-60 POWER STEERING



**Description**

POWER STEERING PUMP  
 2 QUART SEE THROUGH POWER STEERING  
 RESERVOIR  
 SYNTHETIC 75W-90 FRONT AXLE LUBE

**Front Suspension**

12,000# MONO TAPERLEAF FRONT  
 SUSPENSION  
 MAINTENANCE FREE RUBBER BUSHINGS -  
 FRONT SUSPENSION  
 NO FRONT SUSPENSION SPRING BRACKET  
 OPTIONS  
 FRONT SHOCK ABSORBERS

**Rear Axle and Equipment**

RS-21-160 21,000# R-SERIES SINGLE REAR  
 AXLE  
 6.14 REAR AXLE RATIO  
 IRON REAR AXLE CARRIER WITH STANDARD  
 AXLE HOUSING  
 MXL 17T MERITOR EXTENDED LUBE MAIN  
 DRIVELINE WITH HALF ROUND YOKES  
 NO DRIVELINE GUARD  
 DRIVER CONTROLLED TRACTION  
 DIFFERENTIAL - SINGLE REAR AXLE  
 (1) DRIVER CONTROLLED DIFFERENTIAL LOCK  
 REAR VALVE FOR SINGLE DRIVE AXLE  
 BLINKING LAMP WITH EACH MODE SWITCH,  
 DIFFERENTIAL UNLOCK WITH IGNITION OFF,  
 ACTIVE <5 MPH  
 MERITOR 16.5X7 Q+ STAMPED SPIDER CAM  
 REAR BRAKES, DOUBLE ANCHOR, FABRICATED  
 SHOES  
 NON-ASBESTOS REAR BRAKE LINING  
 BRAKE CAMS AND CHAMBERS ON FORWARD  
 SIDE OF DRIVE AXLE(S) WITH AUXILIARY  
 SUPPORT BRACKETS  
 CONMET CAST IRON REAR BRAKE DRUMS  
 REAR BRAKE DUST SHIELDS  
 REAR OIL SEALS  
 WABCO TRISTOP D LONGSTROKE 1-DRIVE  
 AXLE SPRING PARKING CHAMBERS  
 MERITOR AUTOMATIC REAR SLACK  
 ADJUSTERS

Description	
	SYNTHETIC 75W-90 REAR AXLE LUBE
<b>Rear Suspension</b>	
	23,000# 52 INCH VARIABLE RATE MULTI-LEAF SPRING REAR SUSPENSION WITH LEAF SPRING HELPER SPRING SUSPENSION - NO AXLE SPACERS STANDARD AXLE SEATS IN AXLE CLAMP GROUP
<b>Brake System</b>	
	AIR BRAKE PACKAGE WABCO 4S/4M ABS WITHOUT TRACTION CONTROL REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES FIBER BRAID PARKING BRAKE HOSE STANDARD BRAKE SYSTEM VALVES STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM STD U.S. FRONT BRAKE VALVE RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE BW AD-9 BRAKE LINE AIR DRYER WITH HEATER AIR DRYER FRAME MOUNTED STEEL AIR BRAKE RESERVOIRS CLEAR FRAME RAILS FROM BACK OF CAB TO FRONT REAR SUSPENSION BRACKET, BOTH RAILS OUTBOARD BW DV-2 AUTO DRAIN VALVE WITHOUT HEATER ON ALL TANK(S)
<b>Trailer Connections</b>	
	UPGRADED CHASSIS MULTIPLEXING UNIT UPGRADED BULKHEAD MULTIPLEXING UNIT NO HIGH CURRENT TRAILER/BODY CABLE
<b>Wheelbase &amp; Frame</b>	
	6100MM (240 INCH) WHEELBASE 11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI 1425MM (56 INCH) REAR FRAME OVERHANG FRAME OVERHANG RANGE: 51 INCH TO 60 INCH

#### Description

CALC'D BACK OF CAB TO REAR SUSP C/L (CA) :  
 127.2 in  
 CALCULATED EFFECTIVE BACK OF CAB TO  
 REAR SUSPENSION C/L (CA) : 124.2 in  
 CALC'D FRAME LENGTH - OVERALL : 325.39  
 CALC'D SPACE AVAILABLE FOR DECKPLATE :  
 127.2 in  
 CALCULATED FRAME SPACE LH SIDE : 177.14  
 in  
 CALCULATED FRAME SPACE RH SIDE : 159.67  
 in  
 SQUARE END OF FRAME  
 FRONT CLOSING CROSSMEMBER  
 STANDARD WEIGHT ENGINE CROSSMEMBER  
 STANDARD MIDSHIP #1 CROSSMEMBER(S)  
 STANDARD REARMOST CROSSMEMBER  
 STANDARD SUSPENSION CROSSMEMBER

#### Chassis Equipment

THREE-PIECE 14 INCH STEEL CENTER BUMPER  
 WITH FLEXIBLE PLASTIC ENDS  
 FRONT TOW HOOKS - FRAME MOUNTED  
 BUMPER MOUNTING FOR SINGLE LICENSE  
 PLATE  
 FENDER AND FRONT OF HOOD MOUNTED  
 FRONT MUDFLAPS  
 GRADE 8 THREADED HEX HEADED FRAME  
 FASTENERS  
 NO TIRE PRESSURE CONTROL/SENSOR

#### Fuel Tanks

50 GALLON/189 LITER SHORT RECTANGULAR  
 ALUMINUM FUEL TANK - LH  
 RECTANGULAR FUEL TANK(S)  
 PLAIN ALUMINUM/PAINTED STEEL  
 FUEL/HYDRAULIC TANK(S) WITH PAINTED  
 BANDS  
 FUEL TANK(S) FORWARD  
 PLAIN STEP FINISH  
 FUEL TANK CAP(S)  
 DETROIT FUEL/WATER SEPARATOR WITH  
 WATER IN FUEL SENSOR AND HAND PRIMER

Description	
	EQUIFLO INBOARD FUEL SYSTEM HIGH TEMPERATURE REINFORCED NYLON FUEL LINE
<b>Tires</b>	
	HANKOOK AH37 11R22.5 16 PLY RADIAL FRONT TIRES
	HANKOOK DL11 11R22.5 16 PLY RADIAL REAR TIRES
<b>Hubs</b>	
	CONMET PRESET PLUS PREMIUM IRON FRONT HUBS
	CONMET PRESET PLUS PREMIUM IRON REAR HUBS
<b>Wheels</b>	
	ACCURIDE 28828 22.5X8.25 10-HUB PILOT 6.18 INSET 2-HAND HD STEEL DISC FRONT WHEELS
	ACCURIDE 28828 22.5X8.25 10-HUB PILOT 2-HAND HD STEEL DISC REAR WHEELS
	NO RIM/WHEEL TIRE PRESSURE SENSOR
	FRONT WHEEL MOUNTING NUTS
	REAR WHEEL MOUNTING NUTS
<b>Cab Exterior</b>	
	154 INCH BBC HIGH-ROOF ALUMINUM CONVENTIONAL CREW CAB
	RUBBER CAB MOUNTS
	FRONT-REMOVABLE GRILLE MOUNTED BUGSCREEN
	LH AND RH GRAB HANDLES
	PAINTED PLASTIC GRILLE
	ARGENT SILVER HOOD MOUNTED AIR INTAKE GRILLE
	FIBERGLASS HOOD
	SINGLE 14 INCH ROUND HADLEY AIR HORN UNDER LH DECK
	DUAL ELECTRIC HORNS
	SINGLE HORN SHIELD
	DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME WITH (4) KEYS
	REAR LICENSE PLATE MOUNT END OF FRAME
	INTEGRAL HEADLIGHT/MARKER ASSEMBLY

#### Description

(5) AMBER MARKER LIGHTS  
 DAYTIME RUNNING LIGHTS  
 INTEGRAL STOP/TAIL/BACKUP LIGHTS  
 STANDARD FRONT TURN SIGNAL LAMPS  
 DUAL WEST COAST BRIGHT FINISH MIRRORS  
 DOOR MOUNTED MIRRORS  
 102 INCH EQUIPMENT WIDTH  
 LH AND RH 8 INCH BRIGHT FINISH CONVEX  
 MIRRORS MOUNTED UNDER PRIMARY  
 MIRRORS  
 STANDARD SIDE/REAR REFLECTORS  
 DUAL LEVEL CAB ENTRY STEPS ON BOTH  
 SIDES  
 63X14 INCH TINTED REAR WINDOW  
 TINTED DOOR GLASS LH AND RH WITH TINTED  
 NON-OPERATING WING WINDOWS  
 RH AND LH ELECTRIC POWERED WINDOWS  
 TINTED WINDSHIELD  
 2 GALLON WINDSHIELD WASHER RESERVOIR  
 WITHOUT FLUID LEVEL INDICATOR, FRAME  
 MOUNTED

#### Cab Interior

OPAL GRAY VINYL INTERIOR  
 MOLDED PLASTIC DOOR PANEL  
 MOLDED PLASTIC DOOR PANEL  
 BLACK MATS WITH SINGLE INSULATION  
 FORWARD ROOF MOUNTED CONSOLE WITH  
 UPPER STORAGE COMPARTMENTS WITHOUT  
 NETTING  
 IN DASH STORAGE BIN  
 (2) CUP HOLDERS LH AND RH DASH  
 GRAY/CHARCOAL FLAT DASH  
 SMART SWITCH EXPANSION MODULE  
 2-1/2 LB. FIRE EXTINGUISHER  
 FIRST AID KIT  
 HEATER, DEFROSTER AND AIR CONDITIONER  
 STANDARD HVAC DUCTING  
 MAIN HVAC CONTROLS WITH RECIRCULATION  
 SWITCH  
 STANDARD HEATER PLUMBING

#### Description

DENSO HEAVY DUTY AIR CONDITIONER  
 COMPRESSOR  
 BINARY CONTROL, R-134A  
 STANDARD INSULATION  
 SOLID-STATE CIRCUIT PROTECTION AND  
 FUSES  
 12V NEGATIVE GROUND ELECTRICAL SYSTEM  
 DOOR ACTIVATED DOME/RED MAP LIGHTS,  
 FORWARD LH AND RH AND REAR LH, RH AND  
 CENTER  
 LH AND RH ELECTRIC DOOR LOCKS  
 (2) 12 VOLT POWER RECEPTACLES MOUNTED  
 IN DASH  
 TRIANGULAR REFLECTORS KIT WITHOUT  
 FLARES SHIPPED LOOSE IN CAB  
 BASIC HIGH BACK AIR SUSPENSION DRIVER  
 SEAT WITH MECHANICAL LUMBAR AND  
 INTEGRATED CUSHION EXTENSION  
 2 MAN TOOL BOX MID BACK NON SUSPENSION  
 PASSENGER SEAT  
 LH AND RH INTEGRAL DOOR PANEL ARMRESTS  
 VINYL WITH VINYL INSERT DRIVER SEAT  
 VINYL WITH VINYL INSERT PASSENGER SEAT  
 BLACK SEAT BELTS  
 ADJUSTABLE TILT AND TELESCOPING  
 STEERING COLUMN  
 4-SPOKE 18 INCH (450MM) STEERING WHEEL  
 DRIVER AND PASSENGER INTERIOR SUN  
 VISORS

#### Instruments & Controls

GRAY DRIVER INSTRUMENT PANEL  
 GRAY CENTER INSTRUMENT PANEL  
 ENGINE REMOTE INTERFACE WITH PARK  
 BRAKE AND NEUTRAL INTERLOCKS  
 BLACK GAUGE BEZELS  
 LOW AIR PRESSURE INDICATOR LIGHT AND  
 AUDIBLE ALARM WITH (1) ADDITIONAL PARK  
 SWITCH FOR CUSTOMER USE  
 (1) SINGLE BRAKE APPLICATION AIR GAUGE  
 2 INCH PRIMARY AND SECONDARY AIR  
 PRESSURE GAUGES

# **Description**

INTAKE MOUNTED AIR RESTRICTION  
 INDICATOR WITHOUT GRADUATIONS  
 97 DB BACKUP ALARM  
 ELECTRONIC CRUISE CONTROL WITH  
 SWITCHES IN LH SWITCH PANEL  
 KEY OPERATED IGNITION SWITCH AND  
 INTEGRAL START POSITION; 4 POSITION  
 OFF/RUN/START/ACCESSORY  
 ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS, 28  
 LED WARNING LAMPS AND DATA LINKED  
 HEAVY DUTY ONBOARD DIAGNOSTICS  
 INTERFACE CONNECTOR LOCATED BELOW LH  
 DASH  
 2 INCH ELECTRIC FUEL GAUGE  
 ENGINE REMOTE INTERFACE WITH MULTIPLE  
 SET SPEEDS  
 ENGINE REMOTE INTERFACE CONNECTOR AT  
 BACK OF CAB  
 ELECTRICAL ENGINE COOLANT TEMPERATURE  
 GAUGE  
 2 INCH TRANSMISSION OIL TEMPERATURE  
 GAUGE  
 ENGINE AND TRIP HOUR METERS INTEGRAL  
 WITHIN DRIVER DISPLAY  
 (1) DASH MOUNTED PTO SWITCH WITH  
 INDICATOR LAMP  
 NO LANE DEPARTURE WARNING SYSTEM  
 ELECTRIC ENGINE OIL PRESSURE GAUGE  
 OVERHEAD INSTRUMENT PANEL  
 AM/FM/WB WORLD TUNER RADIO WITH  
 BLUETOOTH AND USB AND AUXILIARY INPUTS,  
 J1939  
 DASH MOUNTED RADIO  
 (2) RADIO SPEAKERS IN CAB  
 AM/FM ANTENNA MOUNTED ON FORWARD LH  
 ROOF  
 ELECTRONIC MPH SPEEDOMETER WITH  
 SECONDARY KPH SCALE, WITHOUT  
 ODOMETER  
 STANDARD VEHICLE SPEED SENSOR  
 ELECTRONIC 3000 RPM TACHOMETER  
 NO VEHICLE PERFORMANCE MONITOR  
 NO DETROIT CONNECT SERVICES SELECTED

#### Description

NO ZONAR SERVICES SELECTED  
IDLE LIMITER, ELECTRONIC ENGINE  
TWO ON/OFF ROCKER SWITCHES IN THE DASH  
WITH INDICATOR LIGHTS AND WIRE ROUTED  
TO CHASSIS AT BACK OF CAB, LABEL OPT  
PRE-TRIP LAMP INSPECTION, ALL OUTPUTS  
FLASH, WITH SMART SWITCH  
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH  
DRIVER DISPLAY  
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR  
WITH DELAY  
MARKER LIGHT SWITCH INTEGRAL WITH  
HEADLIGHT SWITCH  
ONE VALVE PARKING BRAKE SYSTEM WITH  
WARNING INDICATOR  
SELF CANCELING TURN SIGNAL SWITCH WITH  
DIMMER, WASHER/WIPER AND HAZARD IN  
HANDLE  
INTEGRAL ELECTRONIC TURN SIGNAL  
FLASHER WITH HAZARD LAMPS OVERRIDING  
STOP LAMPS  
NO MISCELLANEOUS GAUGES

#### Design

PAINT: ONE SOLID COLOR

#### Color

CAB COLOR A: N0006EA WHITE ELITE SS  
BLACK, HIGH SOLIDS POLYURETHANE CHASSIS  
PAINT  
NO FUEL TANK CABINET PAINT  
POWDER WHITE (N0006EA) FRONT  
WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)  
POWDER WHITE (N0006EA) REAR  
WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)  
BUMPER PAINT: FP24812 ARGENT SILVER  
DUPONT FLEX  
STANDARD E COAT/UNDERCOATING

#### Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES  
CABS AND GLIDER KITS

#### Secondary Factory Options



---

**Description**

CORPORATE PDI CENTER IN-SERVICE AND  
OPTION INSTALLATION/MODIFICATION

**Extended Warranty**

TOWING: 1 YEAR/UNLIMITED MILES/KM EXTENDED TOWING  
COVERAGE \$550 CAP FEX APPLIES

**Dealer Installed Options**

	<b>Weight Front</b>	<b>Weight Rear</b>
HD INDUSTRIES POT HOLE PATCH UNIT TCM 425 DHE PER ATTACHED SPECS MOUNTED AND DELIVERED WITH TRAINING	0	0
CLEAR DRIAN AIR DRYER SYSTEM	0	0
Total Dealer Installed Options	0 lbs	0 lbs